

# JET 550

Frontlit / 560 g/m<sup>2</sup>



## ● APPLICATIONS

- **One side printing**
- **Digital printing:** solvent / eco-solvent / UV and Latex inks
- **Screenprinting:** solvent and UV inks
- **Indoor / Outdoor:** Billboards / banners / signage / POS / wall covering

## ● PRODUCT PACKAGING

- **Super Wide format:** 2.50m / 2.78m / 3.20m  
Rolls of: 60 ml / printable side outside
- **Wide Format:** 0.76m / 1.06m / 1.37m / 1.52m / 1.62m / 2.50m / 3.20m  
Rolls of: 30 ml / printable side outside
- **Screenprinting:** 0.90m / 1.00m / 1.10m  
Packaging: 4 rolls of 60 ml / pallet / printable side outside  
2.50m / 2.78m / 3.20m  
Rolls of 60 ml / printable side outside

## ● PRODUCT CHARACTERISTICS

<b>Weight</b>	<b>560 g/m<sup>2</sup></b>		
<b>Coating</b>	PVC coating System LOWICK	<b>Base cloth</b>	High tenacity polyester 1100 Dtex
<b>Colour</b>	White 7325	<b>Finish</b>	Satin inkjet lacquer One side
<b>Thickness</b>	0.47 mm	<b>Translucency XP T 54 199</b>	6 %
<b>Tensile strength NF EN ISO 1421</b>	210 / 200 daN	<b>Tear strength DIN 53363</b>	25 / 20 daN
<b>Temperature stability</b>	-30°C to +70°C -22°F to + 158°F	<b>Adhesion NF EN ISO 2411</b>	7 daN/5cm
<b>F / R</b>	DIN 75 200		

